# SAFETY DATA SHEET

SUPER GLUE



# **SECTION 1. PRODUCT INFORMATION**

Product Name: SUPER GLUE Product Class: SILICONE SEALANT Product Code: SP-1013 Healthy Rating: 2 Flammability rating: 1 Reactivity Rating: 1 Fire: 1

PPE: B

# **SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT: Ethyl cyanoacrylate

<mark>%</mark> 60-100 CAS NO. 7085-85-0 **OSHA PEL** 

None

ACGIH TLV 0.2ppm TWA

# **SECTION 3. INGREDIENT IDENTIFICATION**

**Emergency Overview:** 

Bond skin in seconds

May cause eye and respiratory irritation

Combustible Liquid and Vapor

## **Routes of Entry:**

oral, dermal, inhalation

### **Potential Health Effects:**

### Eyes:

Irritating to the eyes. Causes excessive tearing. Eyelids may bond.

### Skin:

Bonds skin in seconds. May cause skin irritation.

Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic reaction is rare. Cyanoacrylates generate heat on solidification.

In rare circumstances, a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.

## Ingestion:

Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.

## Inhalation:

Exposure to vapors above established exposure limit results in respiratory irritation which may lead to difficulty in breathing and tightness in the chest.

# **SECTION 4. FIRST AID MEASURES**

#### Eyes:

Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect, which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days.

Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped Behind the eyelid cause abrasive damage.

### Skin:

Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.

#### Ingestion:

Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing by separating mass.

#### Inhalation:

Remove to fresh air. If discomfort persists seek medical attention.

## **SECTION 5. FIRE FIGHTING MEASURES**

Health: Flammability: Reactivity: <2,2,1>

Extinguishing Media: Foam, CO2, Dry chemical (B-C)

Flammable Limits in air: Not determined

Flash Point: 65C-93.4C (150F-200F)

Unusual Fire and Explosion Hazards: None

#### **Special Firefighting Procedures:**

Firefighters should wear positive pressure self-contained breathing apparatus

## Hazardous Decomposition Products:

Trace amount of toxic or irritating fumes may be released and the use of breathing apparatus is recommended.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

#### **Accidental Release Measures:**

-Ventilate area.

- -Prevent product from entering the drains.
- -Do not use cloth for mopping up.
- -Flood with water to complete polymerization and scrape off the floor.
- -Cured materials can be disposed of as non-hazardous wastes.

## **SECTION 7 HANDLING AND STORAGE**

-Avoid contact with eyes, skin and clothing.

-Avoid breathing vapor and mist.

-Wash thoroughly after handling. Avoid contact with fabric or paper goods.

-Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors and cause thermal burns.

See label on product for use directions.

## **SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**

#### **Engineering Controls:**

Use positive downdraft exhaust ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

## **Respiratory Protection:**

Use Splendor approved respirator if there is potential to exceed exposure limits..

## **Eye Protection:**

Chemical splash goggles or safety glasses with side shields.

## **Skin Protection:**

Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Colorless gel.
Physical State:	Gel
PH as supplied:	Not applicable.
Special Gravity (H2O = 1):	1.1
Solublity in water:	Polymerizes in presence of water.
Evaporation Rate:	Not available
Boiling Point:	> 149C (300F)
Vapor Pressure:	<0.2mm Hg
% VOC:	20g/L

## **SECTION 10. STABILITY AND REACTIVITY**

Stability:	Stable under recommended storage conditions.	
Conditions to avoid:	Spontaneous polymerization.	
Hazardours Polymerization:	Rapid exothermic polymerization will occur in the presence of	water,
	amines, alkalis and alcohols.	
Incompatability:	Water, amines, alkalis and alcohols.	

## **SECTION 11. TOXICOLOGICAL INFORMATION**

TOXICOLOGICAL INFORMATION: Acute oral LD50 >5000mg/kg, rat (estimated). LD50 >2000mg/kg, rabbit (estimated).

See also Section 3 Hazard Identifications.

SECTION 11 NOTES: Contact Regulatory Affairs if further information is required.

## **SECTION 12. ECOLOGICAL INFORMATION**

ECOLOGICAL INFORMATION: No data available.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Dispose in accordance with federal, state or local regulations.

# **SECTION 14. TRANSPORT INFORMATION**

**U.S. DEPARTMENT OF TRANSPORTATION** 

**PROPER SHIPPING NAME:** Combustible liquids N.O.S (Cyanoacrylate ester)

HAZARD CLASS: 3

UN NUMBER: NA 1993

PACKING GROUP: III

EXCEPTIONS: (Not more than 450L) Unrestricted

MARINE POLLUTANT: None

NOTE: This product classifies as a Consumer Commodity due to its size and intended use. ORM-D

INTERNATIONAL AIR TRANSPORTATION (ICAO/IATA)

PROPER SHIPPING NAME: Aviation regulated liquids N.O.S (Cyanoacrylate ester)

HAZARD CLASS: 9

UN NUMBER: UN3334

PACKING GROUP: III

EXCEPTIONS: (Not more than 500ml). Unrestricted.

WATER TRANSPORATION (IMO/IMDG)

PROPER SHIPPING NAME: Unrestricted.

# **SECTION 15. REGULATORY INFORMATION**

**U.S. FEDERAL REGULATIONS** 

This product has been labeled according to the Federal Hazardous Substances Act and the associated Consumer Product Safety Regulations.

SPLENDOR INDUSTRY COMPANY LIMITED

Tel:86755-29473960 Fax:86755-29473805 Email:sales@splendorcn.com ADDRESS: A 1601, Splendor New Century, No. 1136, NanShan Road, Shenzhen, China

Disclaimer of Liability: The information contained herein is based on the data available to us and, is to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we assume no liability for damages incurred by use of this material. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which may exist. Users of this product should satisfy themselves that the conditions and methods of use assure the product is used safely. No representations or warranties, either expressed or implied, or any nature are made hereunder with respect to the information contained herein. It is the responsibility of the user to comply with any and all federal, state, or local laws and regulations which may exist. Nothing contained herein is to be construed as a recommendation for use in violation of any applicable laws or regulations.