

SAFETY DATA SHEET

Tire rejuvenator



SECTION 1: Identification of the substance/mixture and of the company/undertaking

PRODUCT NAME: Tire rejuvenator
Product type : Aerosol.

Details of the supplier of the safety data sheet

SHENZHEN SPLENDOR INDUSTRY COMPANY LIMITED
Address: Room 409, A Area, Huameiju Business Center,
Baoan District, Shenzhen, China
TEL: 0086-755-29473960
FAX: 0086-755-61637550

e-mail address of person responsible for this MSDS : sales2@doubleagle.com.cn

SECTION 2: Hazards identification

Extremely flammable.

CLASSIFICATION F+;R12.

HUMAN HEALTH

See section 11 for additional information on health hazards.

SECTION 3: Composition/information on ingredients

Name	EC No.	CAS-No.	Content	Classification
BUTANE/PROPANE BLEND	270-704-2	68476-85-7	10-30%	F+;R12.
DIETHANOLAMINE	203-868-0	111-42-2	<0.1%	Xn;R22,R48/22 Xi;R38,R41
DIETHYLENE GLYCOL	203-872-2	111-46-6	<0.1%	Xn;R22
SODIUM LAURYL SARCOSINATE		137-16-6	1-5%	Xi;R41.

The Full Text for all R-Phrases are Displayed in Section 16

SECTION 4: First aid measures

GENERAL INFORMATION

Remove affected person from source of contamination. Get medical attention immediately!

INHALATION

Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Bring these instructions. Place unconscious person on the side in the recovery position and ensure breathing can take place.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Immediately transport to hospital or eye specialist.

Tire rejuvenator

SECTION 5: Firefighting measures

EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Beware, risk of formation of toxic and corrosive gases.

SPECIFIC HAZARDS

In case of fire, toxic and corrosive gases may be formed.

PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately.

SECTION 6: Accidental release measures

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills, beware of slippery floors and surfaces.

ENVIRONMENTAL PRECAUTIONS

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

SPILL CLEAN UP METHODS

For waste disposal, see section 13. When dealing with a spillage, please consult the section relating to suitable protective measures. Absorb spillage with non-combustible, absorbent material. Ventilate well. Prevent discharge of larger quantity to drain.

SECTION 7: Handling and storage

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place.

STORAGE CLASS

Flammable liquid storage.

SECTION 8: Exposure controls/personal protection

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANE/PROPANE BLEND	WEL	1000 ppm	1750 mg/m3	1250 ppm	2180 mg/m3	
DIETHANOLAMINE	OES	3 ppm	15 mg/m3			
DIETHYLENE GLYCOL	WEL	23 ppm	101 mg/m3			

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

Wear suitable respiratory protection. Check that mask fits tight and change filter regularly.

HAND PROTECTION

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Protection against this substance requires special consideration.

Tire rejuvenator

SECTION 8: Exposure controls/personal protection

EYE PROTECTION

Wear tight-fitting goggles or face shield.

OTHER PROTECTION

Provide eyewash station. AVOID ALL SKIN AND RESPIRATORY CONTACT!

HYGIENE MEASURES

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet.

SKIN PROTECTION

Protection suit must be worn.

SECTION 9: Physical and chemical properties

COLOUR	Milky.		
RELATIVE DENSITY	1.00 - 1.05	pH-VALUE, CONC. SOLUTION	8.0 - 10.0

SECTION 10: Stability and reactivity

STABILITY

No particular stability concerns.

SECTION 11: Toxicological information

HEALTH WARNINGS

This chemical can be hazardous when inhaled and/or touched. May cause severe internal injury. Vapour from this chemical can be hazardous when inhaled.

ROUTE OF ENTRY

Inhalation. Ingestion. Skin and/or eye contact. Skin absorption.

SECTION 12: Ecological information

ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

SECTION 13: Disposal considerations

GENERAL INFORMATION

When handling waste, consideration should be made to the safety precautions applying to handling of the product. Only experts should be permitted to carry out disposal of this material.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Absorb spillage with non-combustible, absorbent material.

Tire rejuvenator

SECTION 14: Transport information

GENERAL

Full protective clothing should be worn when handling this product.



UK ROAD CLASS	2.1		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	#
ADR CLASS NO.	2.1	ADR CLASS	Class 2: Gases
ADR PACK GROUP	#	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	#	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PACK GR.	#
EMS	F-D, S-U	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1950
AIR CLASS	2.1	AIR PACK GR.	#

SECTION 15: Regulatory information

LABELLING



Extremely Flammable

RISK PHRASES

R12 Extremely flammable.

SAFETY PHRASES

A1	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.
S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

DETERGENT LABELLING

5 - < 15%	Aliphatic hydrocarbons
< 5%	Anionic surfactants
	Perfumes
Contains	Benzisothiazolinone,LIMONENE,Methylisothiazolinone

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

Tire rejuvenator

SECTION 16: Other information

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

ISSUED BY

HS&E Manager.

REVISION DATE 19/09/2005

REV. NO./REPL. SDS GENERATED 7

RISK PHRASES IN FULL

- R12 Extremely flammable.
- R22 Harmful if swallowed.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.
- R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.

DISCLAIMER

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.